

Enrolladores de tubos electrohidráulicos de 2 carril con enganche frontal de los tubos

Modello Model Modèle Modell Modelo	A	B	Lunghezza max. avvolgibile (mm) e connessioni Max. reel length (mm) and connections Long. max. pouvant être enroulée (mm) et connexions Maximale Wickellänge (mm) und Verbindungen Longitud máx. enrollable (mm) y conexiones				N° contatti N° contacts Nombre de contacts Kontaktanzahl N° contactos	Peso Weight Poids Gewicht Peso
			Ø mm	mm	Ø 3/16"	Ø 1/4"	Ø 5/16"	Ø 3/8"
* 4.096.001	200	65	2000	1500	—	—	2 + 4	8,5
* 4.096.002	270	65	—	2500	2500	1800	2 + 4	10,2
* 4.096.003	300	65	—	4000	3400	2700	2 + 4	11
* 4.096.004	325	65	—	5000	4300	3500	2 + 4	12
* 4.096.005	385	65	—	7000	6500	5500	2 + 4	14
* 4.096.006	235	65	—	2000	—	—	2 + 4	9
* 4.096.007	340	65	—	5200	4500	4000	2 + 4	13

* Per tubi con raccordo ad occhio e rondelle "bonded-seals"

* For hoses with eye-fitting and "bonded-seals" washers

* Pour des tuyaux avec raccord à oeillet et rondelles "bonded-seals"

* Für Schläuche mit Auge-Kupplung und "bonded-seals" Scheiben

* Por tubos con unión de ojete y arandelas "bonded-seals"



Modello Model Modèle Modell Modelo	A	B	Lunghezza max. avvolgibile (mm) e connessioni Max. reel length (mm) and connections Long. max. pouvant être enroulée (mm) et connexions Maximale Wickellänge (mm) und Verbindungen Longitud máx. enrollable (mm) y conexiones				N° contatti N° contacts Nombre de contacts Kontaktanzahl N° contactos	Peso Weight Poids Gewicht Peso
			Ø mm	mm	—	* Ø 1/4"	* Ø 5/16"	* Ø 3/8"
4.097.001	325	70	—	4000	3500	3000	2 + 12	17
4.097.002	385	70	—	6000	5500	5000	2 + 12	19,5
4.097.003	400	70	—	7200	6000	5500	2 + 12	20,3
4.097.004	420	70		8400	7500	6500	2 + 12	21,5
4.097.005	470	70		11000	9500	8000	2 + 12	23

* Per tubi con: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - massimo contatti 2 + 5
* For hoses with: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - contacts max. 2 + 5
* Pour des tuyaux avec: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - max. contacts 2 + 5
* Für Schläuchemit: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - Kontakt max. 2 + 5
* Por tubos con: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - contactos máx. 2 + 5

The technical drawing shows two views of a mechanical component:

- Front View (Left):** A side profile showing a total width of 177. The width is divided into sections B and C. A vertical dimension of 40 is indicated at the bottom left.
- Top View (Right):** A plan view showing a rectangular shape with overall dimensions of 80 by 55. It features four circular holes arranged in a 2x2 grid. The diameter of each hole is labeled as Ø 11. A leader line points from the text "2 X 1/4\" & 3/8\"" to the holes, indicating their size and quantity.

Modello Model Modèle Modell Modelo	A	B	Lunghezza max. avvolgibile (mm) e connessioni Max. reel length (mm) and connections Long. max. pouvant être enroulée (mm) et connexions Maximale Wickellänge (mm) und Verbindungen Longitud máx. enrollable (mm) y conexiones				N° contatti N° contacts Nombre de contacts Kontaktanzahl N° contactos	Peso Weight Poids Gewicht Peso
			Ø mm	mm	—	* Ø 1/4"	* Ø 5/16"	* Ø 3/8"
4.098.000	470	80	—	11000	9500	8000	2 + 12	32,8
4.098.001	500	80	—	12500	11000	10000	2 + 12	32,8
4.098.002	530	80	—	14500	13000	11000	2 + 12	34,4
4.098.003	560	80	—	16000	15000	12500	2 + 12	36,8
4.098.004	625	80	—	21500	18000	16000	2 + 12	41
4.098.005	715	80	—	—	25000	22000	2 + 12	44,5
4.098.006	790	80	—	—	—	27000	2 + 12	47

* Per tubi con: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - massimo contatti 2 + 5
* For hoses with: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - contacts max. 2 + 5
* Pour des tuyaux avec: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - max. contacts 2 + 5
* Für Schläuche mit: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - Kontakt max. 2 + 5
* Por tubos con: Ø 1/4" - Ø 5/16" - 3 + 7 Ampere - contactos máx. 2 + 5